

Commeo HV-C Smart Power System | 209 V | 13.2 kWh esr20U200B2C112E4P8

Technical data

technology description	Lithium ion battery system (NMC)		
communication interface	CAN-Bus Ethernet		
nom. energy	13.2 kWh		
nom. voltage	209.0 V ---		
nom. capacity	63.3 Ah		
max. discharge power (at nom. voltage)	41.7 kW		
expected cycles	(0.8C charge 3.2C discharge 25 °C 80 % SOH) 1,200 @ 100 % DoD		
expected operating life (calendric)	12 years		
installation site	indoors non-condensing		
IP Code	IP 20 (increasing IP Code by using optional accessories)		
protection class	2		
interconnection	3P4S		
standard scope of delivery	energy storage block esbC112P		8 qty
	energy storage block esbC112E		4 qty
	control unit ccuHV200U		1 qty
	Rittal industry cabinet (600 x 2000 x 600 mm) excl. base		1 qty
	accessories		
weight	approx. 261.8 kg		
EU directives	2006/66/EG (BattG), 2014/30/EU (EMC), 2014/35/EU (LVD), 2011/65/EU, 2015/863/EU (RoHS)		
norms and standards	DIN EN 62619, UN 38.3, DIN EN 61010-1, DIN EN 61000-6-2/4, DIN EN ISO 13849-1		

Operating window

operation mode			guided by the State-of-Power (SoP) according to the specifications of the battery management system (BMS)
max. charge current			50.6 A (0.8C)
end-of-charge current			3.2 A (0.05C)
max. discharge current			200.0 A (3.2C)
rel. humidity			< 80 % (temperature-dependent) non-condensing
operating temperature range			5 – 45°C charge 5 – 55 °C discharge
operating voltage range			191.0 – 233.0 V ---
temperature range	transport	< 1 month	-20 – 40 °C
	storage	< 6 month	-20 – 25 °C
max. operating altitude			2,000 m above sea level

 The user manual has to be strictly followed. The operating window of the battery has to be complied with.